



UP TO
18 SEER2

ECO
SERIES



Automatic Restart



Sleep Mode



High Quality



Silent Operation

HIGH-EFFICIENCY DUCTLESS MINI SPLIT COOLING SYSTEMS

FEATURES

- High-Efficiency Cooling Tubes
- Gold Fin Protection
- Fireproof Electrical Control Box
- Refrigerant Leak Detection
- Energy Saver
- ECO Mode
- Smart Diagnosis
- Super Ionizer



GOLD fin



Guaranteed well-being, backed by quality.

UP TO
18 SEER2

ECO
SERIES



Indoor Unit		WS-ECO12C(I)	WS-ECO12(I)	WS-ECO18(I)	WS-ECO24(I)	
Outdoor Unit		WS-ECO12C(O)	WS-ECO12(O)	WS-ECO18(O)	WS-ECO24(O)	
Capacity and Efficiency Specifications	Power Supply	115V~/60Hz/1P	208-230V~/60Hz/1P	208-230V~/60Hz/1P	208-230V~/60Hz/1P	
	Cooling Capacity	Btu/h	12000(2050~12625)	12,000 (2730~12625)	18000(4095~19500)	24000(5120~24900)
	EER	W/W	2.81	2.78	2.82	2.81
	SEER		16	16	16	16
	Moisture removal		13	13	18	2.5
	Refrigerant		R410A/430g	R410A/430g	R410A/430g	R410A/430g
	Suitable area	m2	15~23	15-23	20~35	30~50
Electrical Data	Voltage Range	V	105~125	165~265	165~265	165~265
	Rated current	A	113(2.0~3.0)	9.5 (1.0~10.0)	8.9(1.3~12.0)	11.8(1.5~3.5)
	Rated Input (Cooling)	W	1250(200~1450)	1265 (220~1500)	1870(300~2100)	2500(350~2800)
	Max Current	A	13	10	12	13.5
	Max Power Input (Cooling)	W	1450	1500	2100	2800
Noise Level	Indoor Noise Level - High	dB(A)	38	38	43	49
	Indoor Noise Level - Medium	dB(A)	34	36	38	45
	Indoor Noise Level - Low	dB(A)	30	33	33	41
	Outdoor Noise Level	dB(A)	52	52	52	52
Indoor Unit	Net Dimensions (WD×H)	mm	777×250×201	777×250×201	910×294×206	1010×315×220
	Packing Dimensions (VD×H)	mm	840×315×260	840×315×260	979×372×277	1096×390×297
	Net Weight	kg	8	8	8	11.5
	Gross Weight with Pipe	kg	10	10	12	14.5
Outdoor Unit	Net Dimensions (WD×H)	mm	777×290×498	712×276×459	853×349×602	853×349×602
	Packing Dimensions (VD×H)	mm	818×325×515	765×310×481	890×385×628	890×385×628
	Net Weight	kg	21	18	26	29.5
	Gross Weight with Pipe	kg	24	21	30	33.5
Cooling Pipe	Liquid / Gas	inch				
	Maximum straight distance	m	15	15	20	25
	Maximum height difference	m	8	8	10	15
Electric Supply Cable	Power Supply Cable		#12×3	#12×3	#12×3	#12×3
	Communication cable		#14×4	#14×4	#14×4	#14×4
Thermostat and Temperature Settings	Thermostat type		Remote control	Remote control	Remote control	Remote control
	Operating temperature	°F	63~86	63~86	63~86	63~86
	indoor unit temperature	°F	63~90	63~90	63~90	63~90
	outdoor unit temperature	°F	34~122	34~122	34~122	34~122



GOLD fin



Guaranteed well-being, backed by quality.



Jardines de Cuscatlán
Calle L-7, Polígono F #25
Ciudad Merliot
Antiguo Cuscatlan

(Proximamente)
Lomas de San Francisco
Calle cumbres de cuscatlan, 105
F Sur San Salvador